ROUGH TERRAIN FORKLIFTS

# MAST SELECTIONS & LIFT HEIGHTS

| MODEL | LIFT HEIGHT | STAGES | OVERALL HEIGHT LOWERED | OVERALL HEIGHT EXTENDED | FREE LIFT |
|---|---|---|---|---|---|
| H4 | 10' | 2 | 98 in | 158 in | None |
| H5 | 12' | 2 | 113 in | 183 in | None |
| | 14' FL | 3 | 95 in | 215 in | **58 in** |
| H6 | 10' | 2 | 100 in | 164 in | None |
| | 11' | 3 | 80 in | 166 in | None |
| | 15' | 2 | 125 in | 212 in | None |
| | 16' | 3 | 100 in | 228 in | None |
| | 20' FL | 3 | 117 in | 277 in | **80 in** |
| | 22' | 3 | 125 in | 300 in | None |
| | 28' | 3 | 146 in | 372 in | None |
| H8 | 10' | 2 | 100 in | 164 in | None |
| | 11' | 3 | 80 in | 166 in | None |
| | 15' | 2 | 125 in | 212 in | None |
| | 16' | 3 | 100 in | 228 in | None |
| | 20' FL | 3 | 117 in | 277 in | **80 in** |
| | 22' | 3 | 125 in | 300 in | None |
| H10 H12 | 15' | 2 | 125 in | 212 in | None |
| | 22' | 3 | 125 in | 300 in | None |

FL = free lift mast. Top of overhead guard is approx. 102 in on all units.

## HOW OUR MASTS LIFT

Free lift masts use a single lift cylinder for the first stage, so forks rise without raising the mast. Every mast uses a pair of cylinders for the main lift.

## NEED A DIFFERENT HEIGHT?

Every mast listed has a valid part number. Some carry longer lead times or added cost. We can engineer additional heights for your application. Talk to your HARLO dealer.